



23

Model

6400

000

Bulletin No. C282B

0



## MODELS 6400 6500 6600 6600

- High 1,000-lb/450-kg capacity
- Two platform sizes available for regular or bariatric size wheelchairs
- Two indicator types available for basic or multifunctional weighing
- Guide handles and integral wheels for mobility
- Drive-up ramps included for two-way easy access

🚯 Bluetooth

Wi-Fi/Bluetooth models available





Wi/Fi

# CAP

#### SUITABLE FOR WEIGHING PATIENTS IN WHEELCHAIRS, CHAIRS, OR STANDING

DETECTO's low-profile portable wheelchair scale line offers you eight different models to choose from based on whether you need to weigh patients in regular size or bariatric wheelchairs and whether you need basic weighing functions or more complex patient measurement operations.

The platform is only 2.2 in / 5.6 cm high for easy patient accessibility and comfort while weighing either standing or in a wheelchair. With a high 1,000 lb / 450 kg capacity, the scales are capable of measuring patients of virtually any Model weight possible.

6500

For single-pass weighing to save time, choose the models 6500 or BRW1000 which utilize the MedVue indicator. You can enjoy the timesaving benefits of these scales by using the convenient pushbutton or keypad tare which allows you to remove the wheelchair weight all in one pass.

ACCOMMODATE **BARIATRIC-S** 

VHEELCHAI

MODELS 6600 AND BRW

> Model BRW1000

> > The models 6600 and BRW1000 offer a large 40-in/

> > 101-cm wide platform for use

with bariatric-size wheelchairs.

Despite their size, these wheelchair scales are amazingly easy to handle.

1358. 5 1.3 2 1.2 HEARUE FOR YO

0

Units locking into Kilograms or Pounds helps prevent dosing errors.

transport or vertical

• Two-way ramps for

accessibility from both sides Flexible cable remote display extends up to 14 ft / 4.2 m from scale to

indicator

storage

Quick and easy

mobility for

- Battery power for easy mobility (or use with optional AC adapter)
- Black rubber mat included on the scale platform and ramp for superior traction


Vertical Mode for Easy Transport or Storage



The 6500 and BRW1000 models offer optional connectivity with Welch Allvn Connex vital signs monitors for quick and easy EMR.







136.8.

٢

5' 1.3' 2 (2 \* HEAFUE FOR YOU • 1 1 1 10 • 1 1 1 10

0

### EASES THE PATIENT MEASUREMENT WORK OF DOCTORS AND NURSES

Model BRW1000

#### **FLEXIBLE WIRED** WEIGHT DISPLAY

Since the display is connected to the scale by a long coiled cable that extends up to 14 ft / 4.2 m, it can be positioned where the healthcare professional can most easily read the results.

By using the versatile mounting bracket that comes with each scale, you may permanently mount the indicator on a wall for long-term static use or set it on a tabletop or desk for more mobile type weighing.

The Thin 2.2 in/5.6 cm **Platform Eases** Loading and Unloading



#### **Two Integral Handles Guide Transport**



#### YOUR CHOICE **OF DIGITAL KEYPAD WEIGHING FUNCTIONS**



alphanumeric patient ID entries and 99 stored

(English, Spanish, French, and German).

wheelchair tare weights. Displays in four languages

The MedVue® multifunctional indicator with alphanumeric keypad and RS232 and USB ports displays Height, Weight, and Body Mass Index onscreen simultaneously. Wi-Fi/Bluetooth models are also available for wireless EMR/EHR connectivity. Capable of 14-digital

#### Models 6400/6600



Model 750 indicator with easyto-use, basic weighing functions. BMI calculation, RS232 serial port, and big bold LCD digits.

#### **Two Integral Wheels** for Easy Mobility



#### INCLUDES VERSATILE INDICATOR MOUNTING BRACKETS



The MedVue's<sup>®</sup> ballmount swivel bracket for the back of the indicator allows wall-mount or mobile tabletop weighing with adjustable viewing.



The 750 mounting bracket snaps onto the back of the indicator for wall-mount or mobile tabletop weighing.

## PORTABLE UNITELCHAIR SCALES WITH TIME-SAVING AND PATIENT COMFORT BENEFITS

		10		10		10	- 1000	ka
Model	6400	6400-C	6500	6500-C	6600	6600-C	BRW1000	BRW1000-C
Capacity	1,000 lb x 0.2 lb / 450 kg x 0.1 kg							
Platform Size	32 in x 36 in x 2.2 in / 81 cm x 91 cm x 5.6 cm			32 in x 40 in x 2.2 in / 81 cm x 101 cm x 5.6 cm				
Ramp Size	36 in (91 cm) W x 7.9 in (20.2 cm) L each			40 in (101 cm) W x 7.9 in (20.2 cm) L each				
Cable Length	6 ft / 1.8 m coiled cable, 14 ft / 4.2 m fully extended (from scale to indicator)							
Power	Optional model 6800-1045 AC adapter or 6 AA batteries (not included)		Optional model MV1PWR AC adapter or 6 C batteries (not included)		Optional model 6800-1045 AC adapter or 6 AA batteries (not included)		Optional model MV1PWR AC adapter or 6 C batteries (not included)	
Indicator	Model 750		MedVue <sup>®</sup> Model MV1		Model 750		MedVue <sup>®</sup> Model MV1	
Indicator Dimensions	6.1 in W x 6.8 in H x 1.8 in D / 15.5 cm W x 17.2 cm H x 4.6 cm D		9.8 in W x 6.8 in H x 1.8 in D / 24.9 cm W x 17.2 cm H x 4.6 cm D		6.1 in W x 6.8 in H x 1.8 in D / 15.5 cm W x 17.2 cm H x 4.6 cm D		9.8 in W x 6.8 in H x 1.8 in D / 24.9 cm W x 17.2 cm H x 4.6 cm D	
LCD Digits	0.7 in / 19 mm high LCD, 6 digit, 7 segment		0.9 in / 22 mm high LCD, 5 digit, 7 segment		0.7 in / 19 mm high LCD, 6 digit, 7 segment		0.9 in / 22 mm high LCD, 5 digit, 7 segment	
Keypad Buttons	ON/OFF, ZERO, LOCK/ RELEASE, BMI/ENTER, PRINT, arrow keys		ON/OFF, ZERO, LOCK/ RELEASE, NET/GROSS, TARE, ID/HEIGHT, BMI, PRINT/ ENTER, alphanumeric keys		ON/OFF, ZERO, LOCK/ RELEASE, BMI/ENTER, PRINT, arrow keys		ON/OFF, ZERO, LOCK/ RELEASE, NET/GROSS, TARE, ID/HEIGHT, BMI, PRINT/ ENTER, alphanumeric keys	
Connectivity	RS232 serial	Wi-Fi/ Bluetooth	RS232 serial and USB	RS232 serial, USB, and Wi- Fi/Bluetooth	RS232 serial	Wi-Fi/ Bluetooth	RS232 serial and USB	RS232 serial, USB, and Wi- Fi/Bluetooth
Operating Temperature	14 to 104 °F / -10 to +40 °C							
Net Weight	109 lb / 49 kg		112 lb / 50 kg		117 lb / 53 kg		120 lb / 54 kg	
Shipping Weight	112 lb / 51 kg		115 lb / 52 kg		120 lb / 54 kg		123 lb / 56 kg	
Guide Handles	2 included							
Transport Wheels	2 included							
Country of Origin	USA							
UPC Code	809161302400	809161321005	809161139204	809161325003	809161302509	809161325201	809161139303	809161320008

DETECTO reserves the right to improve, enhance, or modify features and specifications without prior notice.



102 East Daugherty St., Webb City, MO 64870 USA Toll-Free: (800) 641-2008 E-mail: detecto@cardet.com www.Detecto.com

#### SOLD BY: