

6745 DIGITAL BABY SCALE



- 1 gram divisions
- 30 lb / 15 kg capacity
- Roomy 22 in x 9 in / 57 cm x 23 cm weighing tray (flat portion)
- Full-color, touchscreen 3.2 in (diagonal) display with 320 x 240 resolution
- Fun, colorful animal graphics attractive for children
- · Milk and Diaper stored tare weights

- (6) C batteries (not included) or AC adapter (included)
- Integral measuring tape (22 in / 56 cm long)
- Wide supportive scale base for infant safety
- 8-digit numeric patient ID for EMR/EHR
- · Memory key to store and recall a weight
- Built-in carrying handles
- Metric only 6745KG model is also available













6745 DIGITAL BABY SCALE





MEASURING TAPE

0-22 in / 0-56 cm length measuring tape imprinted underneath the clear thermoplastic platform, so will never wear off during use.

PATIENT ID					
12345678 Key in the numeric patient ID to be transmitted when the Print key is pressed.		1	2	3	
		4	5	6	
		7	8	9	
SAVE	CANCEL	0		DEL	

PATIENT ID

The 6745's touchscreen graphics display allows you to enter up to an 8-digit numeric identification number for the patient, which can be sent to an EMR/EHR system.



CONNECTIVITY

Ports include 9-pin RS232 for sending data to a serial printer and USB-B for connecting with a PC for EMR/EHR, plus Wi-Fi and Bluetooth wireless connectivity is standard.

Capacity	6745	0 - 10 lb x 0.002 lb / 10 - 30 lb x 0.005 lb 0 - 10 lb x 0.02 oz / 10 - 30 lb x 0.05 oz 0 - 5 kg x 0.001 kg / 5 - 15 kg x 0.002 kg	
	6745KG	0 - 5 kg x 0.001 kg / 5 - 15 kg x 0.002 kg	
Platform Size (Flat Portion)	22.5 in W x 9.1 in D / 57.1 cm W x 23.1 cm D		
Overall Dimensions	26 in W x 15.1 in D x 7.5 in H / 66 cm W x 38.4 cm D x 19.0 cm H		
Display Type	3.2 in / 81.3 mm (diagonal) full-color TFT display 320 x 240 resolution		
Touch Screen	Resistive touch panel covering the display		
Keys	Mechanical switch type, Power, Zero, Lock/Release, ID, Cycle Display Mode, Menu, Print		
Power Requirements	Models 6745 and 6745KG: Six C-size Alkaline, Ni-Cad, or NiMH batteries (not included) or model 6800-1045 100 to 240 VAC 50/60Hz 12V DC 1.2A UL/CSA power supply with US plug (included). Models 6745EU and 6745UK: Six C-size Alkaline, Ni-Cad, or NiMH batteries (not included) or model 6800-1047 multi-pin AC adapter (included).		
Operating Environment	Operated Temperature Range: 50 to 104°F (+10 to +40°C) Humidity: 0 to 90% non-condensing		
Communication Interfaces	Wi-Fi, Bluetooth 5.0, RS232, and USB-B		
Shipping Weight	35 lb / 15.8 kg		







StableSENSE adjustable filtering to compensate for baby movements



SOLD BY: