


TSSP Series

Load Cells for Bench Applications

Specialty Single Point



- Moisture-proof barrier protection
- Stainless steel construction

MECHANICAL DATA

Rated Capacity, (R.C.) E _{max}	45 lb / 20 kg, 110 lb / 50 kg, 160 lb / 75 kg, 220 lb / 100 kg 440 lb / 200 kg (200kg wide) 507 lb / 230 kg
Minimum Dead Load	4.4 lb / 2 kg
Safe Load Limit	150% R.C.
Ultimate Load	300% R.C.
Deflection at R.C.	.008 in / 0.2 mm
Net Weight	1.97 lb / .9 kg

CERTIFICATE DATA

Issuing Body	OIML
Certificate Number	R60/2000-NL1-04.20
Accuracy Class	C3
Maximum Number of Load Cell Intervals, n _{max}	3,000
Single/Multiple	S
Minimum Load Cell Verification Interval V _{min}	.1 oz / 2.8 g, .2 oz / 7 g, .3 oz / 10 g, 1 oz / 28 g

Cardinal Scale's TSSP specialty single point series is a high performance and low cost load cell for use in bench scales, medical scales, and a variety of other applications. These low-profile load cells are constructed from high-grade (17-4) stainless steel and are easy to install. Available in capacities ranging from 45 to 507 lb / 20 to 230 kg, they feature integral mounting boss. All critical components and wiring are encapsulated to protect against moisture and to insure stable operation of the TSSP in harsh environments. OIML certified.

ELECTRICAL DATA

Rated Output	2±10.0% mV/V
Excitation Voltage, Minimum	12 VDC
Excitation Voltage, Maximum	20 VDC
Cable Length	10 ft / 3 m
Terminal Resistance Excitation Signal	435 ±10 ohms 350 ±5 ohms
Zero Load Output	±1% R.C.
Insulation Resistance	>5000 megohms at 50 VDC

ENVIRONMENTAL DATA

Temperature Compensation Range	-10 to +40°C
Operating Temperature Range	-25 to +50°C
Construction & Protection Code	IP65
Barometric Pressure Effect on	<1 v (min)/1kPa

TSSP Series

Specialty Single Point

Load Cells for Bench Applications





Models Available:



TSSP-20KG, TSSP-50KG TSSP-75KG, TSSP-100KG TSSP-230KG, TSSP-200KGW













Certificate of Conformance Number **R60/2000-NL1-04.20**

VCAP CERTIFIED

Cardinal Scale has been formally audited and found to be fully compliant with the Verified Conformity Assessment Program (VCAP) administered by the National Type Evaluation Program (NTEP) of the National Conference on Weights and Measures (NCWM).

 $Cardinal Scale \ reserves \ the \ right to \ improve, enhance or \ modify features \ and \ specifications \ without \ prior \ notice. All \ registered \ trademarks \ are \ the \ property \ of \ their \ respective \ owners.$

Cardinal Scale Manufacturing Co.
203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001
www.CardinalScale.com

SOLD BY:

